

## Duragloss™ Floor Finish 17% NV Solids

Economical finish for low-maintenance programs.



Item #	Description	Size	Units Per Case
18463	Duragloss™ Floor Finish 17% NV Solids	Gallon	4
18464	Duragloss™ Floor Finish 17% NV Solids	Pail	1-5 GL PA

### Features

- High gloss, tough and durable
- Use with or without burnishing
- Resists black heel marks and scuffing
- Low mop drag and outstanding leveling
- Universally compatible formula
- Use with or without a sealer
- Fast drying, curing and recoating
- Meets industry guidelines for slip resistance
- Coverage: 2,500–3,000 sq. ft./gallon



## Duragloss™ Floor Finish 17% NV Solids

Duragloss™ is a unique fast-drying metal interlock floor finish that provides exceptionally good appearance and wear characteristics. It levels easily and dries quickly to a durable film and provides outstanding resistance to black heel marks, scuffing, maintenance cleaning and heavy traffic. Duragloss is a blend of extremely hard, new-generation acrylic terpolymers, thermoplastics, resins and plasticizers designed to provide exceptional durability, gloss and reflection. Duragloss achieves high levels of hardness and clarity. It builds gloss quickly and responds with unmatched brilliance to burnishing by 1,000- to 3,000-rpm machines. Burnishing is not required to maintain its high gloss.

### Physical Data

Physical form: Milky white liquid  
Odor: Sweet  
Non-volatile solids: 17% minimum  
Total solids: 22%  
pH: 8.0–9.0  
Film color: Colorless  
Freeze/thaw stability: Excellent  
Shelf life: 2 years minimum in unopened container

### Performance Data

Drying time: 15–20 minutes  
Recoat time: 20–30 minutes  
Specular gloss (60°): 90° minimum  
Slip resistance: Meets ASTM D-2047  
Water resistance: Excellent  
Detergent resistance: Excellent  
Adhesion: Excellent, without cracking, powdering or peeling  
Leveling: Excellent  
Scratch resistance: Excellent  
Propane burnishing: Excellent response  
Removability: Easy to remove  
Normal coverage: 2,500–3,000 square feet per gallon on resilient tile