

## Hard Rock™ Floor Sealer

Undercoat sealer compatible with most all-floor finishes.



Item #	Description	Size	Units Per Case
CEB5501	Hard Rock™ Floor Sealer	Gallon	4
CEB5505	Hard Rock™ Floor Sealer	Pail	1-5 GL PA

### Features

- Outstanding adhesion
- Use as a sealer or finish
- Excellent on old, worn and porous floors
- Use with or without burnishing
- High gloss
- Resists black heel marks and scuffing
- Works on most surfaces with most maintenance methods
- Universally compatible with nearly all finishes
- Meets industry guidelines for slip resistance
- Coverage: 2,500–3,000 square feet per gallon



## Hard Rock™ Floor Sealer

Hard Rock Sealer™ is a highly durable, water-based, acrylic polymer floor sealer that forms an excellent sealing and bonding undercoat for a variety of floor surfaces, including vinyl and asphalt tile, linoleum, terrazzo, brick, ceramic tile and quarry tile. Not compatible for cork or unsealed wood. Hard Rock Sealer may also be used as a combination undercoat sealer and top coat finish, affording excellent detergent, blackmarking and slip resistance with an attractive gloss.

### Physical Data

Physical form: Milky white liquid

Odor: Sweet

Non-volatile solids: 16.0% minimum

Total solids: 22%

pH range: 7.5–9.0

Film color: Colorless

Normal coverage: 2,500–3,000 square feet per gallon (min.)

Freeze/thaw stability: Excellent

Shelf life: 2 years minimum in unopened container

### Performance Data

Drying time: 20 minutes

Recoat time: 30–40 minutes

Specular gloss (60°): 85° minimum

Slip resistance: Meets ASTM D-2047

Water resistance: Excellent

Detergent resistance: Excellent

Adhesion: Excellent, without cracking, powdering or peeling

Leveling: Excellent

Scratch resistance: Excellent

Propane burnishing: Excellent response

Removability: Easy to remove