



Duragloss™ Floor Finish 17% NV Solids

Economical finish for
low-maintenance programs

MFG #	Description	Size	Units per carton
CEB5201	Duragloss™ Floor Finish 17% NV Solids	Gallon	4 GL/CT
CEB5205	Duragloss™ Floor Finish 17% NV Solids	Pail	1-5 GL PA

Features

- High gloss, tough and durable
- Use with or without burnishing
- Resists black heel marks and scuffing
- Low mop drag and outstanding leveling
- Universally compatible formula
- Use with or without a sealer
- Fast drying, curing and recoating
- UL listed as to slip resistance
- Coverage: 2,500-3,000 sq. ft./gallon

Online: www.eway.com

Phone: **1.888.203.5101**

Business is Better with Corporate Express Brands



Duragloss™ Floor Finish 17% NV Solids

Duragloss™ is a unique fast-drying metal interlock floor finish that provides exceptionally good appearance and wear characteristics. It levels easily and dries quickly to a durable film and provides outstanding resistance to black heel marks, scuffing, maintenance cleaning and heavy traffic. Duragloss™ is a blend of extremely hard, new generation acrylic terpolymers, thermoplastics, resins and plasticizers designed to provide exceptional durability, gloss and reflection. Duragloss™ achieves high levels of hardness and clarity. It builds gloss quickly and responds with unmatched brilliance to burnishing by 1000 to 3000 rpm machines. Burnishing is not required to maintain its high gloss.

Physical Data

Physical form: milky white liquid
Odor: sweet
Non-volatile solids: 17% minimum
Total solids: 22%
pH range: 8.5
Film color: colorless
Normal coverage: 2500 - 3000 sq. ft. per gallon (min.)
Freeze/thaw stability: keep from freezing
Shelf life: 2 years in original unopened containers

Performance Data

Drying time: 15-20 minutes
Recoat time: 20-30 minutes
Specular gloss (60°): 90 minimum
Slip resistance: UL listed for slip resistance (212s)
Water resistance: excellent (no whitening after 1 hour)
Detergent resistance: excellent
Adhesion: excellent, without cracking, powdering or peeling
Leveling: excellent
Scratch resistance: excellent
Propane burnishing: excellent response
Removability: easy to remove
Normal coverage: 2,500-3,000 sq.ft./gallon on resilient tile.

Online: www.eway.com

Phone: **1.888.203.5101**