



Hard Rock™ Floor Sealer

Undercoat sealer compatible with most all floor finishes

MFG #	Description	Size	Units per carton
CEB5501	Hard Rock™ Floor Sealer	Gallon	4 GL/CT
CEB5505	Hard Rock™ Floor Sealer	Pail	1-5 GL PA

Features

- Outstanding adhesion
- Use as a sealer or finish
- Excellent on old, worn & porous floors
- Use with or without burnishing
- High Gloss
- Resists black heel marks and scuffing
- Works on most surfaces with most maintenance methods
- Universally compatible with nearly all finishes
- UL listed as to slip resistance
- Coverage: 2,500-3,000 sq. ft./gallon

Online: www.eway.com

Phone: **1.888.203.5101**

Business is Better with Corporate Express Brands



Hard Rock™ Floor Sealer

Hard Rock Sealer™ is a highly-durable, water-based, acrylic polymer floor sealer that forms an excellent sealing and bonding undercoat for a variety of floor surfaces, including vinyl and asphalt tile, linoleum, terrazzo, brick, ceramic tile and quarry tile. Not compatible for cork or unsealed wood. Hard Rock Sealer™ may also be used as a combination undercoat sealer and top coat finish, affording excellent detergent, blackmarking and slip resistance with an attractive gloss.

Physical Data

Physical form: milky white liquid
Odor: sweet
Non-volatile solids: 16.0% minimum
Total solids: 22%
pH range: 8.5
Film color: colorless
Normal coverage: 2,500-3,000 sq. ft. per gallon (min.)
Freeze/thaw stability: one freeze/thaw cycle
Shelf life: 2 years in original unopened containers

Performance Data

Drying time: 20 minutes
Recoat time: 30-40 minutes
Specular gloss (60°): 85 minimum
Slip resistance: UL listed for slip resistance (212s)
Water resistance: excellent (no whitening after 1 hour)
Detergent resistance: excellent
Adhesion: excellent, without cracking, powdering or peeling
Leveling: excellent
Scratch resistance: excellent
Propane burnishing: excellent response
Removability: easy to remove

Online: www.eway.com

Phone: **1.888.203.5101**