



Optimum™ Floor Finish 19% NV Solids

High gloss finish when high durability
and low maintenance is desired

MFG #	Description	Size	Units per carton
CEB5681	Optimum™ Floor Finish 19% NV Solids	Gallon	4 GL/CT
CEB5685	Optimum™ Floor Finish 19% NV Solids	Pail	1-5 GL PA

Features

- High gloss, durable finish
- Use with or without burnishing
- Resists black heel marks and scuffing
- Works on most surfaces with most maintenance methods
- Universally compatible formula
- Use with or without a sealer
- UL listed as to slip resistance
- Coverage: 2,500-3,000 sq. ft./gallon

Online: www.eway.com

Phone: **1.888.203.5101**

Business is Better with Corporate Express Brands



Optimum™ Floor Finish 19% NV Solids

Optimum™ provides maximum gloss and durability to extend the life and improve the appearance of floors. Superior scratch, scuff and heel mark resistance is a result of a blend of tough, hard and flexible polymers. It is internally plasticized to give excellent burnish response. This fast drying formulation builds gloss quickly and responds with unmatched brilliance to burnishing by 1000 to 3000 rpm machines. Burnishing is not required to maintain its high gloss and outstanding appearance. Optimum™ achieves levels of hardness and clarity far superior to conventional finishes. The unique copolymerization system in Optimum™ allows it to be used with or without a sealer. Use Optimum™ on almost any type of flooring except unsealed wood, cork or conductive flooring.

Physical Data

Physical form: milky white liquid
Odor: sweet
Non-volatile solids: 19%
Total solids: more than 23%
pH range: 8.5
Film color: colorless
Normal coverage: 2000 - 3000 sq. ft. per gallon (min.)
Freeze/thaw stability: keep from freezing
Shelf life: 2 years in original unopened

Performance Data

Drying time: 20-30 minutes
Recoat time: 30-45 minutes
Specular gloss (60°): 90 minimum
Slip resistance: UL listed for slip resistance (212s)
As measured by ASTM D2047-82
Water resistance: excellent (no whitening after 1 hour)
Detergent resistance: excellent
Adhesion: excellent, without cracking, powdering or peeling
Leveling: excellent
Scratch resistance: excellent
Propane burnishing: excellent response
Removability: easy to remove

Online: www.eway.com

Phone: 1.888.203.5101