

COASTWIDE

Black Magic™

SPECIAL FLOOR FINISH FOR BLACK PLANK FLOORING

**High Gloss Black Floor Sealer-Finish For Black Asphalt Plank Tile Flooring
When High Durability and Low to Medium Maintenance Are Desired**

PRODUCT DESCRIPTION

Black Magic™ was specifically designed to meet the United States Postal Service requirements for a black coating to be used on the black asphalt plank tile flooring used inside postal workrooms and sorting areas. This product meets the standards presented in Specification 4348. Black Magic™ provides maximum gloss and durability to extend the life and improve the appearance of floors. Its superior scratch, scuff and heel mark resistance is a result of COASTWIDE LABORATORIES' proprietary blend of tough, hard and flexible polymers. Burnishing is not required to maintain its high gloss and outstanding appearance. Black Magic™ achieves levels of hardness and clarity far superior to conventional finishes. The unique copolymerization system in Black Magic™ allows it to be used with or without a sealer. CAUTION: This floor finish is a black colored specialty product designed specifically for black colored asphalt plank tile flooring and should NOT be used on any other type or color of flooring.



SPECIAL FEATURES

- High gloss, durable finish.
- Resists black heel marks and scuffing.
- Formulated as a sealer and finish for porous floors.
- Excellent leveling to prevent streaking.
- Dry bright and shines without burnishing.
- Can be spray buffed if preferred.
- More durable than conventional finishes.
- Easy to remove with conventional wax strippers.
- Fast drying to prevent down-time.
- Rejuvenates tile color.
- Use with or without a sealer.

PACKAGE SIZES

PR5075 5 gallon pail

PHYSICAL DATA

Physical Form	Black liquid
Odor	Sweet
Non-Volatile Solids	19%
Total Solids	26%
pH Range	8.0 - 8.5
Film Color	Black
Sediment	No more than 0.08% by volume (max.)
Normal Coverage	2000 - 3000 sq. ft. per gallon (min.)
Freeze/Thaw Stability	Keep from freezing
Shelf Life	2 years in original unopened containers

PERFORMANCE DATA

Drying Time:	20-30 minutes.
Recoat Time:	30-35 minutes.
Specular Gloss (60°):	85 minimum.
Slip Resistance:	UL Listed for slip resistance (.212S).
Water Resistance:	Excellent (no whitening after 1 hour).
Detergent Resistance:	Excellent.
Adhesion:	Excellent, without cracking, powdering or peeling.
Leveling:	Excellent.
Scratch Resistance:	Excellent.
Low Speed (175 rpm):	Very Good Response.
Propane Burnishing:	Excellent Response.
Removability:	Easy to remove.
Normal Coverage:	2,000-3,000 sq.ft./gallon.

YOUR LOWEST TOTAL-COST SUPPLIER

WILSONVILLE	(503) 416-5300
PORTLAND	(503) 288-1582
BEAVERTON	(503) 643-4129
ALBANY	(541) 926-3289
KLAMATH FALLS	(541) 884-0053
EUGENE	(541) 344-5550
MEDFORD	(541) 773-7461



SEATTLE	(206) 624-1225
EVERETT	(425) 339-3724
TACOMA	(253) 475-8940
OLYMPIA	(360) 754-3300
VANCOUVER	(360) 694-7697

Oregon 1-800-775-3289

www.coastwidelabs.com

Washington 1-800-732-1084