

COASTWIDE

Total™

ONE-STEP FLOOR SEALER-FINISH

A One-Step Combination Floor Sealer and Floor Finish With Maximum Finish Durability and Sealing Performance

PRODUCT DESCRIPTION

Total™ is the first floor coating to successfully balance the adhesion and surface sealing characteristics of our best floor sealer with the outstanding gloss and extended impact resistance and durability of our best floor finish. The unique leveling agents in Total™ provide an easy-to-apply floor sealer-finish that works on all types of hard surface floors with virtually every floor maintenance method and equipment. Total™ responds with high, medium and low speed burnishing equipment to build gloss quicker. The shine of Total™ actually improves with repeated burnishing. The specially designed particle size of the polymers provides maximum adhesion and surface sealing performance. Total™ is high impact resistant, easily burnished to a brilliant shine, soil resistant, easily applied without mop drag or streaking, resistant to blackmarking and exhibits high initial and retained gloss.

SPECIAL FEATURES

- Seals and finishes in one easy step.
- Unsurpassed initial and retained gloss.
- Simple to apply.
- Balances outstanding sealer adhesion with unsurpassed finish durability.
- Use with or without burnishing.
- Rapid burnish response.
- Fast drying and quick curing.
- Excellent soil resistance reduces deep scrubbing and stripping.
- Resists blackmarking.
- Outstanding clarity and brightness.
- Coverage 2500-3500 square feet per gallon.
- Universally compatible with most sealers and finishes.
- UL listed as to slip resistance.

PHYSICAL DATA

Physical Form:	Milky white liquid.
Odor:	Sweet.
pH:	8.5 - 9.5.
Non-Volatile Solids:	Minimum 18.5%.
Total Solids:	Over 25%.
Film Color:	Colorless.
Freeze/Thaw Stability:	Three full cycles.
Shelf Life:	2 years in original unopened containers.
Odor Index:	Low.



PACKAGE SIZES

PR5821	4 -1 gallon case
PR5825	5 gallon pail
PR5829	55 gallon drum

PERFORMANCE DATA

Drying Time:	20-30 minutes.
Recoat Time:	30-35 minutes.
Specular Gloss (60°):	90 minimum.
Slip Resistance:	UL Listed and Exceeds ASTM D-2047.
Water Resistance:	Excellent (no white after 8 hours).
Detergent Resistance:	Excellent.
Adhesion:	Excellent, without cracking, powdering or peeling.
Removability:	Easy to remove with conventional wax strippers.
Sediment	0.08% by volume, maximum.

YOUR LOWEST TOTAL-COST SUPPLIER

WILSONVILLE	(503) 416-5300
PORTLAND	(503) 288-1582
BEAVERTON	(503) 643-4129
ALBANY	(541) 926-3289
KLAMATH FALLS	(541) 884-0053
EUGENE	(541) 344-5550
MEDFORD	(541) 773-7461



COASTWIDE
LABORATORIES

Solutions for Industrial and Commercial Cleaning

Serving Our Customers Since 1937

SEATTLE	(206) 624-1225
EVERETT	(425) 339-3724
TACOMA	(253) 475-8940
OLYMPIA	(360) 754-3300
VANCOUVER	(360) 694-7697

Oregon 1-800-775-3289

www.coastwidelabs.com

Washington 1-800-732-1084